

ALL INFORMATION CONTAINED OR DISCLOSED BY THIS DOCUMENT IS CONSIDERED CONFIDENTIAL AND PROPRIETARY BY ANDU ELECTRONICS CO.,LTD. ALL DESIGN, MANUFACTURING, USE, REPRODUCTION, AND ALL SALES RIGHTS, ARE EXPRESSLY RESERVED BY AND TO ANDU ELECTRONICS CO.,LTD. AND COMMUNICATION OF THIS INFORMATION TO OTHERS IS PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF ANDU ELECTRONICS CO.,LTD.

DRAWING REVISIONS

REV	S/N	DESCRIPTION	APPROVED	DATE
A	20070823-1	ORIGINAL RELEASE		

Bottom

Top



字体:Eras Bold ITC 字高: 2.5MM

字体:Verdana 字高: 2.5MM

NOTES: UNLESS OTHERWISE SPECIFIED.

- material:
 - A, Contact:Steel 304
 - B, body: PA 94-V0;
 - C, cover: PC 94-V0;
- removed burrs and sharp edge.
- For ANF、ANG、ANS fuse.
- Suitable rated current: 32VDC 100A.
- RoHS COMPLIANT.
- The fuse holder is capable of functioning individually or in multiple sets;
- Mounting torque: 4.5Nm

Assmebly

window
cover




东莞市赛力特保险丝制造有限公司
DONGGUAN SELITTEL FUSES MFG CO., LTD

RoHS COMPLIANT

UNLESS OTHERWISE STATED

WALL THICKNESS		MM
LINEAR	.XX	±0.15 MM
	.XXX	±0.05 MM
ANGULAR		±0.5 DEG
DRAFT ANGLE/SIDE		0.5 °MAX
BURR & FLASH		0.10 MAX
BREAK CORNERS		0.20 R.MAX
PARTING LINE MISMATCH		0.05 MAX

FUSEHOLDER
FOR ANS ANF ANG

DSGN	Tommy Qiu	07-12-08	SCALE	free		REV	
DFTS	Tommy Qiu	07-12-08	SHEET	1 OF 1			
CHKD			PART NO.		ANS-H		
APPD					A		