

ALL INFORMATION CONTAINED OR DISCLOSED BY THIS DOCUMENT IS CONSIDERED CONFIDENTIAL AND PROPRIETARY BY ANDU ELECTRONICS CO.,LTD. ALL DESIGN, MANUFACTURING, USE, REPRODUCTION, AND ALL SALES RIGHTS, ARE EXPRESSLY RESERVED BY ANDU TO ANDU ELECTRONICS CO.,LTD. AND COMMUNICATION OF THIS INFORMATION TO OTHERS IS PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF SELLER.

DRAWING REVISIONS				
REV	S/N	DESCRIPTION	APPROVED	DATE
A	20110616-1	ORIGINAL RELEASE		
B	20110629-1	Change size from 14.8 to 22.8mm		
C	20130213-1	Change size from 11.2 to 11.5mm		



NOTES: UNLESS OTHERWISE SPECIFIED.

1. material: Spring brass, T=0.3mm; plastic: PBT.
2. finish: Tin plated;
3. removed burrs and sharp edge.
4. For mini blade automotive Fuses.
6. Suitable rated current: 15A.



东莞市赛力特保险丝制造有限公司
DONGGUAN SELITTEL FUSES MFG CO.,LTD

RoHS COMPLIANT

UNLESS OTHERWISE STATED

WALL THICKNESS		MM
LINEAR	.XX	±0.15 MM
	.XXX	±0.05 MM
ANGULAR		±0.5 DEG
DRAFT ANGLE/SIDE		0.5 °MAX
BURR & FLASH		0.10 MAX
BREAK CORNERS		0.20 R.MAX
PARTING LINE MISMATCH		0.05 MAX

FUSE holder

FOR ATS MIN ATM 297 fuse

DSGN		16-6-11	SCALE	free	
DFTS		16-6-11	SHEET	1 OF 1	
CHKD			PART NO.	SL-506P-3	REV C
APPD					