

ALL INFORMATION CONTAINED OR DISCLOSED BY THIS DOCUMENT IS CONSIDERED CONFIDENTIAL AND PROPRIETARY BY ANDU ELECTRONICS CO.,LTD. ALL DESIGN, MANUFACTURING, USE, REPRODUCTION, AND ALL SALES RIGHTS, ARE EXPRESSLY RESERVED BY AND TO ANDU ELECTRONICS CO.,LTD. AND COMMUNICATION OF THIS INFORMATION TO OTHERS IS PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF ANDU

DRAWING REVISIONS				
REV	S/N	DESCRIPTION	APPROVED	DATE
A	20090313-03	ORIGINAL RELEASE		
B	20090410-01	Changed tolerance		

NOTES: UNLESS OTHERWISE SPECIFIED.

1. Applicable: For ATO-N Fuse.
2. Electrical: Rated for current up to 30A32V.
3. Insulating body:Nylon
4. Contact: Brass with Tin plated.
5. With other wire sizes or leangths available on special order, rang: #14-20#.
6. Insulation resistance at 500VDC, Min 100MΩ



 东莞市赛力特保险丝制造有限公司
DONGGUAN SELITTEL FUSES MFG CO., LTD

RoHS COMPLIANT		FUSEHOLDER		CUSTOMER	
UNLESS OTHERWISE STATED		FOR ATO-N			
WALL THICKNESS	MM	DSGN	Tom	12-22-08	SCALE free
LINEAR .XX	± 0.15 MM	DFTS	TOM	12-22-08	SHEET 1 OF 1
LINEAR .XXX	± 0.05 MM	CHKD			PART NO.
ANGULAR	± 0.5 DEG	APPD			SL-703SA
DRAFT ANGLE/SIDE	0.5 MAX				REV B
BURR & FLASH	0.10 MAX				
BREAK CORNERS	0.20 R.MAX				
PARTING LINE MISMATCH	0.05 MAX				